



Solid, simple and smart:
advanced reliability in compressed air

STORMY PRO 1.5-7.5 kW/2-10 hp





STORMY PRO: your work floor companion

The Mark STORMY PRO combines performance with comfort like no other piston compressor. Ultra-quiet and easy to use, the STORMY PRO gives you reliable and powerful pneumatic support right on your work floor. With a power range from 2 to 10 hp, and flexible options for air storage and treatment, a STORMY PRO model is always available to fit your needs.



Extra quiet

Optimized canopy design minimizes sound levels.



Easy to use

Intuitive control panel with pressure gauge and hour counter.



Compact

All-in-one design reduces the unit's footprint.



The integrated quality air solution

If you need dry, high-quality air, the Mark STORMY PRO series is available with an integrated refrigerant dryer for a compact all-in-one solution.



A flexible go-getter

Strong performance

The STORMY PRO packs a punch in a small frame. Its new pump was designed to give you a strong, energy-efficient performance and superior reliability. A dedicated cooling fan ensures smooth operation, even in hot and dusty conditions.



Flexible storage

To ensure stable air delivery, the STORMY PRO offers a range of air storage options. For those with limited space, the floor-mounted unit comes with an integrated 27-liter air vessel. If you need more storage, tank-mounted models are available with 270-liter or 500-liter vessels.

Always dependable

When you have things to do, you can't afford your compressor to break down. The STORMY PRO's high-efficiency piston pump with low rotation speed delivers exceptional reliability and a long lifetime.



The right STORMY PRO to meet your needs

STORMY PRO S27 F2MZ - STORMY PRO S27 F3Z

2-3 hp / 1.5-2.2 kW

- Extra quiet for comfortable work floor operation.
- Easy to operate and maintain.
- Integrated 27-liter air vessel ensures a stable air supply.
- Built for safety with fire-proof insulating foam and metal belt guard.
- Ideal for small pneumatic jobs.

STORMY PRO S100 F3MZ / STORMY PRO S500F5Z

3-5 hp / 2.2-4 kW

- New NS31 pump delivers increased performance and reliability.
- Canopy was designed specifically to minimize sound.
- Available in floor-mounted and tank-mounted (270 and 500-liter) models.
- All-in-one design reduces the unit's footprint.
- Ideal for automotive service stations.

STORMY PRO SF6Z / STORMY PRO S500F10XZD

5.5-10 hp / 4-7.5 kW

- Flexible air storage options with floor-mounted and tank-mounted (270 and 500-liter) models.
- Heavy-duty cooling system with dedicated fan for dependable operation in all conditions.
- Can be outfitted with integrated dryer for an all-in-one quality air solution.
- Ideal for workshops and carpentry shops.



Extra quiet



Compact



Easy to use



Integrated vessel



Improved reliability

STORMY PRO S27 F2MZ - STORMY PRO S27 F3Z 2-3 hp

| Description | Power | Pressure | Pump | Pump RPM | Displacement | Vessel | Noise | Voltage | Dimensions | Weight | Outlet |
|----------------------------|-------|----------|-------|-------------------|--------------|--------|--------|-------------|-------------|--------|------------|
| | HP | bar | Type | Min ⁻¹ | l/min | L. | Lp(4m) | V / ph / Hz | L x W x H | KG | Connection |
| STORMY PRO S27 F2MZ 230/50 | 2 | 10 | NS12S | 1075 | 255 | 27 | 61 | 230/1/50 | 735x430x845 | 86 | 1/4" G |
| STORMY PRO S27 F2Z 400/50 | 2 | 10 | NS12S | 1075 | 255 | 27 | 61 | 400/3/50 | 735x430x845 | 86 | 1/4" G |
| STORMY PRO S27 F3MZ 230/50 | 3 | 10 | NS12S | 1350 | 320 | 27 | 62 | 230/1/50 | 735x430x845 | 87 | 1/4" G |
| STORMY PRO S27 F3Z 400/50 | 3 | 10 | NS12S | 1350 | 320 | 27 | 62 | 400/3/50 | 735x430x845 | 87 | 1/4" G |



High performance



Extra quiet



Flexible storage



Compact



Improved reliability

STORMY PRO S100 F3MZ / STORMY PRO S500F5Z 3-5 hp

| Description | Power | Pressure | Pump | Pump RPM | Displacement | Vessel | Noise | Voltage | Dimensions | Weight | Outlet |
|------------------------------|-------|----------|-------|-------------------|--------------|--------|--------|-------------|---------------|--------|------------|
| | HP | bar | Type | Min ⁻¹ | l/min | L. | Lp(4m) | V / ph / Hz | L x W x H | KG | Connection |
| STORMY PRO S100 F3MZ 230/50 | 3 | 10 | NS19S | 1050 | 393 | 100 | 65 | 230/1/50 | 1002x1227x580 | 220 | 1/2" G |
| STORMY PRO S100 F3Z 400/50 | 3 | 10 | NS19S | 1050 | 393 | 100 | 65 | 400/3/50 | 1002x1227x580 | 220 | 1/2" G |
| STORMY PRO S270s F3MZ 230/50 | 3 | 11 | NS19S | 1050 | 393 | 270 | 65 | 230/1/50 | 1522x580x1242 | 248 | 1/2" G |
| STORMY PRO S270s F3Z 400/50 | 3 | 11 | NS19S | 1050 | 393 | 270 | 65 | 400/3/50 | 1522x580x1242 | 248 | 1/2" G |
| STORMY PRO S270 F3MZ 230/50 | 3 | 11 | NS31 | 1050 | 444 | 270 | 65 | 230/1/50 | 1522x580x1242 | 248 | 1/2" G |
| STORMY PRO S270 F3Z 400/50 | 3 | 11 | NS31 | 1050 | 444 | 270 | 65 | 400/3/50 | 1522x580x1242 | 248 | 1/2" G |
| STORMY PRO SF4Z 400/50 | 4 | 11 | NS31 | 1300 | 553 | 0 | 69 | 400/3/50 | 750x580x710 | 170 | 3/4" G |
| STORMY PRO S270 F4Z 400/50 | 4 | 11 | NS31 | 1300 | 553 | 270 | 69 | 400/3/50 | 1522x580x1242 | 248 | 1/2" G |
| STORMY PRO SF5Z 400/50 | 5 | 11 | NS31 | 1400 | 598 | 0 | 69 | 400/3/50 | 750x580x710 | 170 | 3/4" G |
| STORMY PRO S270F5Z 400/50 | 5 | 11 | NS31 | 1400 | 598 | 270 | 69 | 400/3/50 | 1522x580x1242 | 248 | 1/2" G |
| STORMY PRO S500F5Z 400/50 | 5 | 11 | NS31 | 1400 | 598 | 500 | 69 | 400/3/50 | 1937x600x1348 | 274 | 3/4" G |



- 
High performance
- 
Extra quiet
- 
Flexible storage
- 
Compact
- 
Quality air

STORMY PRO SF6Z / STORMY PRO S500F10XZD 5.5-10 hp

| Description | Power | Pressure | Pump | Pump RPM | Displacement | Vessel | Noise | Voltage | Dimensions | Weight | Outlet |
|------------------------------|-------|----------|------|-------------------|--------------|--------|--------|-------------|---------------|--------|------------|
| | HP | bar | Type | Min ⁻¹ | l/min | L. | Lp(4m) | V / ph / Hz | L x W x H | KG | Connection |
| STORMY PRO SF6Z 400/50 | 5 | 11 | NS39 | 1010 | 660 | 0 | 65 | 400/3/50 | 1000x741x955 | 153 | 3/4" G |
| STORMY PRO SF6XZ 400/50 | 5 | 11 | NS39 | 1010 | 660 | 0 | 65 | 400/3/50 | 1000x741x955 | 157 | 3/4" G |
| STORMY PRO S270F6Z 400/50 | 5 | 11 | NS39 | 1010 | 660 | 270 | 65 | 400/3/50 | 1517x741x1487 | 220 | 1/2" G |
| STORMY PRO S270F6XZ 400/50 | 5 | 11 | NS39 | 1010 | 660 | 270 | 65 | 400/3/50 | 1517x741x1487 | 224 | 1/2" G |
| STORMY PRO S500F6Z 400/50 | 5 | 11 | NS39 | 1010 | 660 | 500 | 65 | 400/3/50 | 1943x741x1593 | 253 | 3/4" G |
| STORMY PRO S500F6XZ 400/50 | 5 | 11 | NS39 | 1010 | 660 | 500 | 65 | 400/3/50 | 1943x741x1593 | 257 | 3/4" G |
| STORMY PRO S500F6ZD 400/50 | 5 | 11 | NS39 | 1010 | 660 | 500 | 65 | 400/3/50 | 1943x767x1596 | 265 | 3/4" G |
| STORMY PRO S500F6XZD 400/50 | 5 | 11 | NS39 | 1010 | 660 | 500 | 65 | 400/3/50 | 1943x767x1596 | 269 | 3/4" G |
| STORMY PRO SF8Z 400/50 | 7 | 11 | NS39 | 1140 | 750 | 0 | 68 | 400/3/50 | 1000x741x955 | 229 | 3/4" G |
| STORMY PRO SF8XZ 400/50 | 7 | 11 | NS39 | 1140 | 750 | 0 | 68 | 400/3/50 | 1000x741x955 | 235 | 3/4" G |
| STORMY PRO S500F8Z 400/50 | 7 | 11 | NS39 | 1140 | 750 | 500 | 68 | 400/3/50 | 1943x741x1593 | 355 | 3/4" G |
| STORMY PRO S500F8XZ 400/50 | 7 | 11 | NS39 | 1140 | 750 | 500 | 68 | 400/3/50 | 1943x741x1593 | 361 | 3/4" G |
| STORMY PRO S500F8ZD 400/50 | 7 | 11 | NS39 | 1140 | 750 | 500 | 68 | 400/3/50 | 1943x767x1596 | 367 | 3/4" G |
| STORMY PRO S500F8XZD 400/50 | 7 | 11 | NS39 | 1140 | 750 | 500 | 68 | 400/3/50 | 1943x767x1596 | 371 | 3/4" G |
| STORMY PRO SF10Z 400/50 | 10 | 11 | NS59 | 810 | 1020 | 0 | 66 | 400/3/50 | 1000x741x955 | 248 | 3/4" G |
| STORMY PRO SF10XZ 400/50 | 10 | 11 | NS59 | 810 | 1020 | 0 | 66 | 400/3/50 | 1000x741x955 | 254 | 3/4" G |
| STORMY PRO S500F10Z 400/50 | 10 | 11 | NS59 | 810 | 1020 | 500 | 66 | 400/3/50 | 1943x741x1593 | 399 | 3/4" G |
| STORMY PRO S500F10XZ 400/50 | 10 | 11 | NS59 | 810 | 1020 | 500 | 66 | 400/3/50 | 1943x741x1593 | 411 | 3/4" G |
| STORMY PRO S500F10ZD 400/50 | 10 | 11 | NS59 | 810 | 1020 | 500 | 66 | 400/3/50 | 1943x767x1596 | 415 | 3/4" G |
| STORMY PRO S500F10XZD 400/50 | 10 | 11 | NS59 | 810 | 1020 | 500 | 66 | 400/3/50 | 1943x1593x738 | 513 | 3/4" G |

YD = star-delta start T = integrated refrigerant dryer



Contact your local representative:

www.mark-compressors.com

6999200540



CARE

Care is what service is all about: professional service by knowledgeable people, using high-quality original parts.

TRUST

Trust is earned by delivering on our promises of reliable, uninterrupted performance and long equipment lifetime.

EFFICIENCY

Equipment efficiency is ensured by regular maintenance. Efficiency of the service organization is how Original Parts and Service make the difference.

© 2020, Mark. All rights reserved. All mentioned brands, product names, company names, trademarks and service marks are the properties of their respective owners. Our products are constantly being developed and improved. We thus reserve the right to modify product specifications without prior notice. Pictures are not contractually binding.

